Technical data sheet

GES9-3B service outlet with handle clamp

Item number: 7405079





Service outlet with handle clamp for up to 12 individual Modul 45 devices in 3 UT4 universal supports, use in trunking systems and system floors for indoor use

Floor covering recess in the hinged cover pre-adjusted to 5 mm, if necessary adjustable to 10 mm.

Up to 9 installation devices with 50 mm central plate can be inserted. Service outlet with handle clamp, 3-compartment, for the installation of MT9 mounting support. Three type APMT5 cover plates can be installed. Floor covering recess in the hinged cover pre-adjusted to 5 mm, if necessary adjustable to





Polyamide

Master data

Item number 7405079 Type GES9-3B U 9011 Description 1 Service outlet Description 2 for universal mounting Manufacturer OBO Dimension 264x264x67 Colour Graphite black; RAL 9011 Material Polyamide Smallest sales unit 1 Unit of quantity Piece		
Description 1 Service outlet Description 2 for universal mounting Manufacturer OBO Dimension 264x264x67 Colour Graphite black; RAL 9011 Material Polyamide Smallest sales unit 1 Unit of quantity Piece	Item number	7405079
Description 2 for universal mounting Manufacturer OBO Dimension 264x264x67 Colour Graphite black; RAL 9011 Material Polyamide Smallest sales unit 1 Unit of quantity Piece	Туре	GES9-3B U 9011
Manufacturer OBO Dimension 264x264x67 Colour Graphite black; RAL 9011 Material Polyamide Smallest sales unit 1 Unit of quantity Piece	Description 1	Service outlet
Dimension 264x264x67 Colour Graphite black; RAL 9011 Material Polyamide Smallest sales unit 1 Unit of quantity Piece	Description 2	for universal mounting
Colour Graphite black; RAL 9011 Material Polyamide Smallest sales unit 1 Unit of quantity Piece	Manufacturer	ОВО
Material Polyamide Smallest sales unit 1 Unit of quantity Piece	Dimension	264x264x67
Smallest sales unit 1 Unit of quantity Piece	Colour	Graphite black; RAL 9011
Unit of quantity Piece	Material	Polyamide
	Smallest sales unit	1
Weight 205 kg	Unit of quantity	Piece
vveight 200 kg	Weight	205 kg
Weight unit kg/100 pc.	Weight unit	kg/100 pc.

Technical data sheet

GES9-3B service outlet with handle clamp

117 1264





Dimensions Length Width 264 mm Height 67 mm

Technical data

Number of installable devices	12
Number of mounting boxes	3
Version for	Square
Cable outlet version	Swivellable cord outlet
Floor covering protection frame	yes
Floor care	Dry
Seal installation option	no
Floor height, min.	73 mm
Suitable for raised floor installation	yes
Suitable for screed-flush closed underfloor ducts	no
Suitable for screed-covered underfloor ducts	yes
Suitable for cavity floor installation	yes
Suitable for wet care	no
Suitable for underfloor box	250/350
Suitable for underfloor ducts	yes
Device support to accept mounting boxes	yes
Length of external dimensions	264 mm
Length of installation dimensions	244 mm
With floor covering recess	yes
Nominal size for device installation units	9
Frame version	Carpet protection frame
Protection rating (IP) when used	IP20
Protection rating (IP) when unused	IP40
Protection rating IK code	IK08
Heavy-duty version	no
Installation system type	UT4
Vertical load, large area	to 5,000 N
Vertical load, small area	to 3,000 N

Technical data sheet

GES9-3B service outlet with handle clamp





Technical data	
Approvals	VDE
Opening mechanism	Handle
Floor covering thickness	5 mm