Technical data sheet

GES9-3S service outlet with locking slider

Item number: 7405085





Service outlet with locking slider for up to 12 individual Modul 45 devices in 3 UT4 universal supports, use in trunking systems and system floors for indoor use

Floor covering recess in the hinged cover pre-adjusted to 5 mm, if necessary adjustable to 10 mm.

Up to 9 installation devices can be used with a 50 mm central plate. Service outlet with locking slider, 3-compartment, for the installation of MT9 mounting support. Three type APMT5 cover plates can be installed.

Floor covering recess in the hinged cover pre-adjusted to 5 mm, if necessary adjustable to 10 mm.





Polyamide

Master data

| Item number | 7405085 |
|---------------------|--------------------------|
| Type | GES9-3S U 9011 |
| Description 1 | Service outlet |
| Description 2 | for universal mounting |
| Manufacturer | OBO |
| Dimension | 264x264x67 |
| Colour | Graphite black; RAL 9011 |
| Material | Polyamide |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 199.5 kg |
| Weight unit | kg/100 pc. |

Technical data sheet

GES9-3S service outlet with locking slider





Dimensions 242 Page 1970 19

Height 67 mm Dimension h 73 mm

Technical data

| Number of installable devices | 12 | |
|---|-------------------------|--|
| Number of mounting boxes | 3 | |
| Version for | Square | |
| Cable outlet version | Swivellable cord outlet | |
| Floor covering protection frame | yes | |
| Floor care | Dry | |
| Seal installation option | no | |
| Floor height, min. | 73 mm | |
| Suitable for raised floor installation | yes | |
| Suitable for screed-flush closed underfloor ducts | no | |
| Suitable for screed-covered underfloor ducts | yes | |
| Suitable for cavity floor installation | yes | |
| Suitable for wet care | no | |
| Suitable for underfloor box | 250/350 | |
| Suitable for underfloor ducts | yes | |
| Device support to accept mounting boxes | yes | |
| Length of external dimensions | 264 mm | |
| Length of installation dimensions | 244 mm | |
| With floor covering recess | yes | |
| Nominal size for device installation units | 9 | |
| Frame version | Carpet protection frame | |
| Protection rating (IP) when used | IP20 | |
| Protection rating (IP) when unused | IP40 | |
| Protection rating IK code | IK08 | |
| Heavy-duty version | no | |
| Installation system type | UT4 | |
| Vertical load, large area | to 5,000 N | |
| Vertical load, small area | to 3,000 N | |

Technical data sheet

GES9-3S service outlet with locking slider





| Technical data | | |
|----------------|--------------------------|----------------|
| | Approvals | VDE |
| | Opening mechanism | Locking slider |
| | Floor covering thickness | 5 mm |