

Technical data sheet

Cable tray GKS GX 60 FT

Item number: 6483033



GKS 60 GX = perforated cable tray system with 60 mm side height
Magnetic shield insulation without cover 20 dB, with cover 50 dB.



- St** Steel
- FT** Hot-dip galvanised

Master data

Item number	6483033
Type	GKS GX 620 FT
Description 1	Cable tray
Manufacturer	OBO
Dimension	60x200x3000
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	3
Unit of quantity	Metre
Weight	200.68 kg
Weight unit	kg/100 m


Technical data sheet

Cable tray GKS GX 60 FT

Item number: 6483033



Dimensions



Length	3,000 mm
Width	200 mm
Height	60 mm
Plate thickness	0.7 mm
Dimension B	200 mm
Dimension D	75 mm
Dimension H	60 mm
Dimension L	3,000 mm

Technical data

Connector version	Without connectors
Mounting system fastening type	Floor Ceiling Wall
Walkable	no
Maintain electrical functions	no
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Usable cross-section	118 cm ²
Usable cross-section	11800 mm ²
Rustproof steel, pickled	no
Side perforation	yes
Wide-span version	no
Load test type according to IEC 61537	Type II
Type of connector, cable support system	Screwed

Technical data sheet


Cable tray GKS GX 60 FT

Item number: 6483033



Loads

Support spacing 1.0 m	0.8 kN/m
Support spacing 1.5 m	0.6 kN/m
Support spacing 2.0 m	0.5 kN/m
Support spacing 2.5 m	0.45 kN/m



Load diagram, cable tray, type GKS GX60

- 1 Permitted cable tray/ladder load in kN/m without man load
- 2 Support width in m
- 3 Rail bend in mm at permitted kN/m
- 4 Load scheme during testing
- Load curve with cable tray/ladder width in mm
- Strut bend curve according to support width