

# Technical data sheet

## GKS GX 60 FS cable tray

Item number: 6480034



GKS 60 GX = perforated cable tray system with 60 mm side height  
Magnetic shield insulation without cover 20 dB, with cover 50 dB.



- St** Steel
- FS** Strip galvanized

### Master data

Item number	6480034
Type	GKS GX 630 FS
Description 1	Cable tray
Manufacturer	OBO
Dimension	60x300x3000
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	3
Unit of quantity	Metre
Weight	339.12 kg
Weight unit	kg/100 m





# Technical data sheet

## GKS GX 60 FS cable tray

Item number: 6480034



### Dimensions



Length	3,000 mm
Width	300 mm
Height	60 mm
Plate thickness	1 mm
Dimension B	300 mm
Dimension D	75 mm
Dimension H	60 mm
Dimension L	3,000 mm

# Technical data sheet

## GKS GX 60 FS cable tray

Item number: 6480034




### Technical data

Connector version	Without connectors
Mounting system fastening type	Floor Ceiling Wall
Walkable	no
Maintain electrical functions	no
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Usable cross-section	178 cm <sup>2</sup>
Usable cross-section	17800 mm <sup>2</sup>
Rustproof steel, pickled	no
Side perforation	yes
Wide-span version	no
Load test type according to IEC 61537	Type II
Type of connector, cable support system	Screwed

### Loads

Support spacing 1.0 m	1.6 kN/m
Support spacing 1.5 m	0.9 kN/m
Support spacing 2.0 m	0.75 kN/m
Support spacing 2.5 m	0.6 kN/m



#### Load diagram, cable tray, type GKS GX60

- 1 Permitted cable tray/ladder load in kN/m without man load
- 2 Support width in m
- 3 Rail bend in mm at permitted kN/m
- 4 Load scheme during testing
- Load curve with cable tray/ladder width in mm
- Strut bend curve according to support width