Technical data sheet

PYROPLUG® MagicBox, three-sided, interior height 110

mm

Item number: 7204170





Fire protection box as insulation system, made of single-part stainless steel housing with intumescent fire protection inlays. Can be used in walls, on raw floors, beneath system floors and as insulation of rising sections in ceilings. Interior can be fully assigned with installations. For interior application. Closure of the residual openings with PYROSIT® NG fire protection foam, particularly simple for difficult geometries. CE-labelled construction product with general type approval. Fire resistance class El90 (fire-resistant). Including graphite strip.

 ϵ

A2

Stainless steel

2E

Bright, treated

Master data

Item number	7204170
Туре	PMB 160-3 A2
Description 1	Fire Protection Box 3-sided
Description 2	with intumescending inlays
Available from	04.10.2022
Manufacturer	OBO
Dimension	300x623x166
Material	Stainless steel
Surface	Bright, treated
Surface standard	
Smallest sales unit	1
Unit of quantity	Piece
Weight	599.4 kg
Weight unit	kg/100 pc.

Technical data sheet

PYROPLUG® MagicBox, three-sided, interior height 110 mm



Technical data





Fire protection version

Accessories required

Internal height Internal width

Shape

Box body

605 mm

yes 115 mm

Rectangular

OBO	17.05.2024