Item number: 7134266






90° bend, horizontal and unperforated, for all cable tray types of 60 mm side height. Fitting, unperforated, in round design. The interior radius of the fitting is 150 mm. Fastening materials should be ordered separately.



Master data

Item number7134266TypeRBU 90 660 A2Description 190° bendDescription 2unperforated, round typeManufacturerOBODimension60x600MaterialStainless steelSurfaceBright, treatedSmallest sales unit1Unit of quantityPieceWeight unitkg/100 pc.		
Description 1 90° bend Description 2 unperforated, round type Manufacturer OBO Dimension 60x600 Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1 Unit of quantity Piece Weight 770 kg	Item number	7134266
Description 2unperforated, round typeManufacturerOBODimension60x600MaterialStainless steelSurfaceBright, treatedSurface standard1Unit of quantityPieceWeight770 kg	Туре	RBU 90 660 A2
ManufacturerOBODimension60x600MaterialStainless steelSurfaceBright, treatedSurface standard	Description 1	90° bend
Dimension60x600MaterialStainless steelSurfaceBright, treatedSurface standard	Description 2	unperforated, round type
Material Stainless steel Surface Bright, treated Surface standard I Smallest sales unit 1 Unit of quantity Piece Weight 770 kg	Manufacturer	OBO
Surface Bright, treated Surface standard 1 Unit of quantity Piece Weight 770 kg	Dimension	60x600
Surface standard 1 Smallest sales unit 1 Unit of quantity Piece Weight 770 kg	Material	Stainless steel
Smallest sales unit 1 Unit of quantity Piece Weight 770 kg	Surface	Bright, treated
Unit of quantity Piece Weight 770 kg	Surface standard	
Weight 770 kg	Smallest sales unit	1
	Unit of quantity	Piece
Weight unit kg/100 pc.	Weight	770 kg
	Weight unit	kg/100 pc.



Width	600 mm
Width	24 in
Height	60 mm
Height	2 in
Plate thickness	1.5 mm
Dimension B	600 mm
Dimension R	150 mm
	•

Item number: 7134266



Technical data

Bend (angle)	90°
Connector version	Without connectors
Maintain electrical functions	no
Mounting perforation in base	no
NATO hole pattern	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Side perforation	no
Wide-span version	no
Type of connector, cable support system	Screwed