

Technical data sheet

CombiController V20 B+C, plug-in arrester 320 V

Item number: 5099847



SurgeController cover – type 1 + 2 surge arrester

- Plug-in cover; upper part can be separated from base without tools
 - Incl. thermal and dynamic cut-off unit and visual display of defects
 - High current conductivity and long service life
- Upper part



Master data

Item number	5099847
Type	V20-B+C 0-320
Description 1	SurgeController V20
Description 2	plug-in arrester
Manufacturer	OBO
Dimension	320V
Smallest sales unit	1
Unit of quantity	Piece
Weight	5.5 kg
Weight unit	kg/100 pc.


Technical data sheet

CombiController V20 B+C, plug-in arrester 320 V



Item number: 5099847

Technical data



Arrester surge current (8/20 μ s) [total]	20 kA
Response time	<25 ns
Version for	1-pin cover; 320 V
Pole version	1
Structural width in division units (division unit, 17.5 mm)	1
Operating temperature, max.	80 °C
Operating temperature, min.	-40 °C
Maximum continuous voltage AC	320
Maximum continuous voltage DC	420
Integrated back-up fuse	no
Conductor cross-section, flexible (fine-wire), min.	25 mm ²
Conductor cross-section, rigid (single-wire/multiwire), max.	35 mm ²
Lightning protection zone LPZ	0→2
Max. mains-side overcurrent protection	125
Maximum back-up fuse	125 A
Maximum discharge current (8/20 μ s)	40 kA
Installation type	On basic element
Nominal discharge current (8/20 μ s)	20 kA
Nominal discharge current (8/20 μ s) [L-N]	20 kA
Nominal voltage AC (50/60 Hz)	320 V
Network form	TN
Test class, type 2	yes
Protection rating	IP20
Protection level	≤1,4
Signalling on device	Visual
SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-1	Class I+II